

SOUTHERN HOIST SERVICES

Unit A, Culverlands Corner, Winchester Road, Shedfield, Southampton, Hants. SO32 2JF

Tel: (01329) 833223 Fax: (01329) 833683

E-mail: sales@southernhoists.co.uk www.southernhoists.co.uk

GEDA 1500ZZPRACK & PINION TRANSPORT PLATFORM



TECHNICAL SPECIFICATIONS

Max carrying capacity	1500kg / 7 person transport 2000kg materials only
Average lifting speed	Material mode - 24m/min Passenger mode – 12m/min
Power requirement	3 phase and neutral 415 volt 32 amp (pp)
Max. working height	100m
Platform dimensions	Variable – see opposite
Weight of base unit	1272kg – 1782kg (dependant upon platform configuration)
Weight of mast section	40kg

A versatile twin mast rack and pinion hoist with endless possibilities in the industry!

Modular construction of this machine allows the client to tailor the hoist to suit the contract. The hoist can either be used as materials only at 24m/min, or with the addition of a roof piece, it can be used to transport personnel at a speed of 12m/min.

An added bonus is the low pull value of the tie, which allows the unit to be tied to scaffold.

Each unit is equipped with an overload sensor and side protection rails on the unloading ramp for safety.

The choice of platform will depend upon your SWL requirements, and the option of single or double ramps.

